

OKINA USA

PTZ
SERIES

SS10W-C100H



Normal light monitoring results



Low illumination color turn B/W effect

- 1/2.8" Sony CMOS CCD, 1000 TV Lines
- 10x Optical Zoom, 10x Digital Zoom (Max 100x Zoom)
- 5~50mm focal length
- 0.01 lux (color) / 0.001 lux (B&W)
- 360° Endless Pan ; 180° Auto-flip Tilt ; 95° Normal Tilt
- 256 Presets ; RS-485 Communication
- Pelco-D & Pelco-P Selectable protocols
- Built-in OSD
- 12V DC

PAL Version also available

10x Mini PTZ

PTZ Dome Camera



SPECIFICATIONS

FC CE RoHS Made in Taiwan

Model	SS10W-C100H
Mount Type	Arm Type Wall Mount
Image Sensor	1/2.8" Sony CMOS
Effective Pixels	1280(H) x 720(V)
Resolution	1000 TV Lines
S/N Ratio	60 dB (Enhanced)
Zoom	x10 Optical Zoom, x10 Digital Zoom
Focal Length	5~50mm
Min. Illumination	Color to B&W, Color: 0.01Lux, B&W: 0.001Lux
Shutter Speed	1/60~1/12000 sec
White Balance	Auto
Back Light Compensation (BLC)	On / Off
Focus	Auto/manual, take high-performance DSP to realize complete digit and ultra-high speed focus function
Presets	256
Patrol Track	4 groups, each can record 200 actions
Cruise Track	Total 30 presets can join cruise, can setting the presets' residence time
Other Scan	Support Horizontal scan, deuce area scan, scan random
Rotation Range	Horizontal 360° unlimited rotation, Vertical 90°, Auto reversal
Rotation Speed	Horizontal & Vertical Min 0.01°, Max 200°/S
Communication	RS-485
Protocols	Pelco-D, Pelco-P
OSD	Yes
Rated Power	12V DC / 2A
Temperature Control	Built-in
Operation Temperature	-4°F ~ 122°F / -20°C~50°C (Select temperature control accessories)
Humidity	<95% RH
Material	Aluminum Shell
Dimension	5.12 (Ø) x 8.66(H) inches / 130 (Ø) x 220 (H) mm

*Specifications and appearance are subject to change without notice.

DIMENSIONS

