

OKINA USA

PTZ
SERIES

SS27HB-V55DN

SP27HB-V55DN

SS27HB-V55DNP

SP27HB-V55DNP




TRUE
DN

SS27HB-V55DN

- High Speed PTZ
- 360° Pan (0.4° ~ 100° per sec)
- 90° Tilt (0.4°-100° per sec) with Aut-flip

SP27HB-V55DN

- **Super High Speed PTZ, 128 Presets**
- 360° Pan (0.4° ~ 320° per sec)
- 90° Tilt (0.4° ~ 150° per sec) with Auto-flip
- 1/4" Sony Double Speed CCD
- 550 TV Lines (Color) / 680 TV Lines (B/W)
- 27x Optical Zoom, f3.5~94.5mm, F1.6~F2.9
- 12x Digital Zoom
- **DNR (Digital Noise Reduction)**
- **Mechanical IR Cut Filter (ICR)**
- 0.4 lux (50 IRE Color) / 0.02 Lux (50 IRE B/W)
- Digital Imagestabilization Function
- Manchester-Code and Coax Control
- Multi-protocol Communication through RS485 Protocol
- IP66 Rating; OSD Menu for Setup & Programming
- 24V AC, 60VA



IR Cut Filter – ICR

P = PAL Version

27x Day & Night

PTZ Dome Camera

27x Day & Night**PTZ Dome Camera****SPECIFICATIONS**
FC CE RoHS Made in Taiwan

P.I.C.	P-041		P-042	
Model	SS27HB-V55DN	SS27HB-V55DNP	SP27HB-V55DN	SP27HB-V55DNP
Signal Format	NTSC	PAL	NTSC	PAL
Mount Type	Wall Mount			
Image Sensor	1/4" Sony Double Speed CCD			
Resolution / DSP	550 TV Lines (Color) / 630 TV Lines (B/W)			
Video Signal	1.0V p-p (Sync Negative), Y/C Output			
Minimum Illumination	0.4 lux (50 IRE Color) / 0.02 Lux (50 IRE B/W)			
Mechanical IR Cut Filter (ICR)	Yes			
Zoom	27x Optical Zoom / 12x Digital Zoom			
Lens	3.5~94.5mm Lens / F1.6~F2.9			
Focus	Auto / Manual			
White Balance	ATW, AWB, manual			
Electronic Shutter Speed	Slow shutter			
Iris Control	Auto / Manual			
Gain Control	Auto / Manual			
OSD	OSD menu for setup & programming via telemetry Date/Time/Zoom/Temperature/Zones(4 privacy zones)/Name			
Pan Speed / Pan Range	0.4° ~ 100° per sec. / 360°		0.4° ~ 320° per sec. / 360°	
Tilt Speed / Tilt Range	0.4° ~ 100° per sec. / 0° ~ 90° with Auto Flip		0.4° ~ 150° per sec. / 0° ~ 90° with Auto-Flip	
Communication	Multiple Protocol through RS485 Protocol			
Preset Positions	128 Presets			
Tour / Sequence	4 Programmable Tours / 4 Patterns			
Heater & Blower	Built-in			
Power	24V AC / 60VA			
Operating Temperature	-4°F ~ 140°F / -20°C ~ 60°C			
Dimension	10.24"(Ø) x 14.17"(H) / 260mm(Ø) x 360mm(H)		11.02"(Ø) x 14.96"(H) / 280mm(Ø) x 380mm(H)	
Weight	8.05 lbs / 3.65 kg		9.92 lbs / 4.5 kg (with bracket)	

*Specifications and appearance are subject to change without notice.