



HD21B24-940



- SDI 1080p - **1920 x 1080**
- 1/2.9" Sony Exmor
- 4.0mm Fixed Lens
- 0.5 Lux
- 24 IR LED
- IR distance up to 50ft / 24m
- 700mA max
- 12V DC

PAL Version also available

HD SDI 1080p WDR DNR

24 IR OSD Bullet Camera



SPECIFICATIONS

FC CE RoHS

Model	HD21B24-940
Image Sensor	1/2.9" Sony Exmor CMOS Sensor
Resolution	Digital; 1920x1080p (1080p/30fps) 1280x720p (720p/60fps)
Total Pixels	2,000(H) x 1,121(V), 2.24M Pixels
Active Pixels	1,936(H) x 1,105(V), 2.12M Pixels
Scanning System	Progressive
Min. Illumination	Color: 0.5 lux , BW: 0.1 lux Color DSS: 0.002 lux , BW DSS: 0.001 lux
Video output	HD SDI
IR LED	24 IR LED
IR Distance	Up to 50ft / 24m
Lens	4.0mm Fixed Lens
Lens Mount	DC / Manual
S/N Ratio	More than 50dB (AGC Off)
Brightness	0 ~ 20 steps
Shutter Speed	Auto / Manual (1/30(1/25) ~ 1/60000)
Flickerless	Off / On
DSS	Off / x2 / x3 / x4
AGC	Off / On
WDR / BLC	Off / WDR / BLC
Day & Night	Auto / Day / Night / Ext
White Balance	Auto / One Push / Manual / Indoor / Outdoor
Sharpness	0 ~ 10 steps
Mirror	Off / H / V / H&V
Freeze	Off / On
E.Zoom	Off / Max x2 ~ x23
HLC	Off / On
ACE	Off / Low / Middle / High
DNR	Off / Low / Middle / High / Auto
D.Compress	Off / On
Privacy	Off / On (24 points)
Motion	Off / On (3 points)
Shading Det	Off / On
Shading	Off / On
Defect Det	One Push (Enter)
Defog	Off / On
HD Format	1080p / 720p
Language	English, Japanese, Chinese
Power Source	12V DC \pm 10%
Power Consumption	150mA max @ Boot up ; 250mA max @ IR on ; 110mA max @ IR off
Operation Temperature	14°F ~ 122°F / -10°C ~ +50°C ; Humidity: 0%RH ~ 80%RH
Storage Temperature	-4°F ~ 140°F / -20°C ~ +60°C ; Humidity: 0%RH ~ 90%RH
Dimensions & Net Weight	6.41(L) x 2.36(W) x 2.36(H) inches / 162.8(L) x 60(W) x 60(H) mm ; 1 lb / 453 g

*Specifications and appearance are subject to change without notice

DIMENSIONS AND PARTS

