



SHDX-755AIDN-VD


SSDX-742AI-VD

SHDX-755AIDN-VDP

SSDX-742AI-VDP

Wall Mount Bracket available

MB-7VD



During low lux situations, a normal lens will easily lose focus. However, an **Aspherical lens** will remain sharp regardless of the lighting conditions.



3-AXIS Design



DN
3-AXIS

SHDX-755AIDN-VD
SHDX-755AIDN-VDP

- 1/3" Sony Super HAD CCD II
- 550 TV Lines, HQ-1
- 2.9mm~10.0mm Aspherical Auto Iris Lens
Made in Japan
- High Gain / Low Noise Amplifier - DNR
- 0.15 Lux @ F1.2
- Day & Night Feature
- IP66 Rating
- 12V DC

SSDX-742AI-VD
SSDX-742AI-VDP

- 1/3" Sony Super HAD CCD
- 420 TV Lines
- 2.9mm~10.0mm Aspherical Auto Iris Lens
Made in Japan
- 0.15 Lux @ F1.2
- IP66 Rating
- 12V DC

P = PAL Version

3-AXIS Day & Night

Vandal Proof Dome Camera



FC CE Made in Taiwan

SPECIFICATIONS

Model Number	SHDX-755AIDN-VD	SHDX-755AIDN-VDP	SSDX-742AI-VD	SSDX-742AI-VDP
TV System	NTSC	PAL	NTSC	PAL
Image Sensor	1/3" Sony Super HAD CCD II		1/3" Sony Super HAD CCD	
DSP	Sony HQ-1		Sony	
Resolution	550 TV Lines		420 TV Lines	
Video Output	1.0V p-p / 75Ω			
Total Pixels	811(H) x 508(V)	795(H) x 596(V)	537(H) x 505(V)	537(H) x 557(V)
Synchronization	Internal			
Minimum Illumination	0.15 Lux @ F1.2 Color mode automatically switches to B/W mode under 2.0 Lux		0.15 Lux @ F1.2	
Day & Night Function	Color/D&N		N/A	
DNR / Sens-up	High Gain / Low Noise Amplifier - DNR		N/A	
S/N Ratio	More than 48dB (AGC off)			
Auto Gain Control	ON/OFF Switchable			
Flickerless	ON/OFF Switchable			
BLC	ON/OFF Switchable			
AES	ON/OFF Switchable			
DC Level	The VR for adjusting the IRIS level of auto iris lens			
White Balance	AWB / 2500°K ~ 9200°K			
Video Output	1 Vp-p composite / 75 Ohms			
Lens / Angle of View	2.9mm~10.0mm Aspherical Auto Iris Lens (Made in Japan) F1.2, 94.6°~28.8°			
Max Breaking Strength	656.1 Kgf			
Lead Free	Yes			
Waterproof Level	IP66			
Power Supply	12V DC			
Power Consumption	145mA / 1.7W		85mA / 1.0W	
Operating Temperature	14°F ~ 122°F / -10°C ~ +50°C			
Dimension	4.42"(Ø) x 5.51"(H) / 112.2(Ø) x 140(H) mm			
Weight	2.09 lbs / 950g			

*Specifications and appearance are subject to change without notice.

DIMENSIONS

